



*Nothing else measures up!*

**Follow us!**



Prospect House  
George Cayley Drive  
Clifton Moor  
York  
England  
YO30 4XE

Tel: +44 (0) 1904 692723  
Fax: +44 (0) 1904 690385

E-Mail: [sales@yorksurvey.co.uk](mailto:sales@yorksurvey.co.uk)



## Temp-Mark

white-yellow



**Code: 16425 - 16426**

## Health & Safety Data Sheet



# Product Safety Data Sheet

## Temp-Mark White & Yellow

### 1 IDENTIFICATION OF PRODUCT & COMPANY

**PRODUCT NAME:** TEMP-MARK 750ml TEMPORARY AEROSOL PAINT  
**INTENDED USE:** No relevant information. For Professional Use Only.  
**SUPPLIER:** York Survey Supply Centre, Prospect House, George Cayley Drive, Clifton Moor Industrial Estate, York, YO30

4XE

**EMERGENCY TELEPHONE:** 01904 692723

### 2 COMPOSITION/INFORMATION OF INGREDIENTS

A blend of pigment(s), water miscible solvent(s), emulsifiers(s), corrosion inhibitor(s), demineralised water and hydrocarbon propellants.

For details of substances presenting a health hazard within the meaning of the Chemicals (Hazard Information & Packing) regulations 1993 see under Section 8 of this Safety Data Sheet.

### 3 HAZARDS IDENTIFICATION

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray on a naked flame or any incandescent material.

Flammable.

### 4 FIRST AID MEASURES

**GENERAL:** In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person

**INHALATION:** Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

**EYE CONTACT:** Contact lenses should be removed, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, seek medical advice.

**SKIN CONTACT:** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.

**INGESTION:** If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 5 FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Powder, Halogenated Hydrocarbons, Sand, Foam.

**NOT TO BE USED:** Water.

**SPECIAL INSTRUCTIONS FOR FIRE FIGHTING PERSONNEL:** Fire will produce dense black smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water courses.

### 6 ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listing in sections 7 & 8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, and place in suitable container for disposal in accordance with the waste regulations. Do not allow large quantities to enter drains or water courses. If it does, local water companies should be contacted, in case of contamination of streams, rivers or lakes, the Environment Agency.

### 7 STORAGE & HANDLING

Avoid skin & eye contact. For personal protection see section 8. Good housekeeping and regular removal of waste materials will minimise risks. Store in accordance with the conditions of the licence which is necessary under the Petroleum (Consolidation) Act. See the HSE guidance note 'Storage of Flammable Liquids in Containers'. Observe the label precautions. Store between 5°C & 25°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. The principles contained in the HSE's guidance note 'Storage of Packaged Dangerous Substances' should be observed when storing this product.

### 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Measures:** Provide adequate ventilation. When reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If extraction methods are insufficient to maintain concentrations of particulates and/or solvent vapours below relevant OELs, suitable respiratory protective equipment should be worn.

**Notes:** Notations: **Sk** - risk of absorption through skin **Sen** - respiratory sensitiser **OES** - Occupational Exposure Standard  
**MEL** - Maximum Exposure Limit OELs are from EH40 except where marked SUP which are assigned by the supplier of the substance.

Substance Name	% Conc. Range	Symbol	OES 8hr ppm	OES 15min ppm	Risk Phrases	Notation
DIMETHYL ETHER	>40% & =<75%	F+	1,000.00		12	OES
PROPAN-2-OL	>0% & =<10%	F	400.00	500.00	11	Sk OES

**General Protection:** All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

**Respiratory Protection:** Air fed respiratory equipment should be worn when sprayed if levels cannot be controlled below OELs and engineering methods cannot be reasonably improved.

**Hand Protection:** Full physical protection is best. Seek relevant advice from glove manufacturers. Barrier cream may be of help but should not be applied after exposure has occurred.

**Eye Protection:** Eye protection designed to protect against liquid splashes should be worn.

**Skin Protection:** Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap & water or a proprietary skin cleaner.

### 9 PHYSICAL & CHEMICAL PROPERTIES

**PHYSICAL STATE:** Opaque white viscous liquid  
**FLASH POINT:**  
**VISCOSITY:**  
**SPECIFIC GRAVITY:** 1.138 gms/cc Method: Weight per gallon cup

**VAPOUR DENSITY:** HEAVIER than Air  
**LOWER EXPLOSION LIMIT:**  
**SOLUBILITY IN WATER:** MISCIBLE

### 10 STABILITY & REACTIVITY

Stable under the recommended storage & handling conditions (see section 7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and acid materials to prevent the possibility of an exothermic reaction.

### 11 TOXICOLOGICAL INFORMATION

There is no data available of the product itself. Repeated or prolonged contact with the skin may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eye may cause irritation and reversible local damage..

### 12 ECOLOGICAL INFORMATION

There is no data available on the product itself. Large quantities of the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

### 13 DISPOSAL CONSIDERATIONS

Do not allow large quantities to enter the drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution & Environmental Protection Acts.

### 14 TRANSPORT INFORMATION

**ROAD/RAIL:** SI Number - 1950  
Class - 2.2

**SEA:** Class - 9  
Marine Pollutant - No  
Ems - 2-13  
Main Risk - FLAMMABLE IMDG PAGE No. 9022  
Sub Risk - HARMFUL  
Shipping Name - AEROSOL DISPENSERS NOS  
UN Number - 1950  
MFAG - 260\*\*\*

### 15 REGULATOR INFORMATION

The product is classified and labelled for supply in accordance with the Chemicals (Hazard Information & Packaging) Regulations as follows.

**Classification** F-Flammable

**Contains**

**Risk Phrases** 10 Flammable

**Safety Phrases** 2 Keep out of reach of children

46 If swallowed seek medical advice immediately and show this container or label.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

16 Keep away from sources of ignition - NO SMOKING

**'P' Phrases** Do not breathe Vapour or Spray

The information contained in this Safety Data Sheet does not constitute the user's own assessment of the workplace risks as required by other health & safety legislation.

The provisions of the Health & Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

### 16 OTHER INFORMATION

Text of any Risk Phrases listed in Section 8

R11 Highly Flammable

R12 Extremely Flammable

**Date of Origination** - 08/06/95

**Date of Last revision** - 08/06/95

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemical (Hazardous Information & Packaging) Regulations. The product should not be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written instructions. As the specific conditions of use of the product are outside of the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this Safety Data Sheet is based on the present state of knowledge and current national legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as an guarantee of technical performance or suitability for particular applications.

**Further information and relevant advice can be found in:**

*The Control Of Substances Hazardous to Health Regulations 1988 (SI 1988:1657)*

*The Manual Handling Operations Regulations 1992 (SI 1992: 2793)*

*Storage of Flammable Liquids in Containers. HS(G)51*

*Storage of Packaged Dangerous Substances. HS(G)71*

*The Environmental Protection (Duty of Care) Regulations 1992 (SI 1988: 2839)*